





ATOM

Cloud-connected high-performance multimedia elevator display

- Display rich, dynamic and web-enabled contents
- Remotely manage all your connected displays
- Playlist and content scheduling
- Remote diagnostics, troubleshooting and live display view



Step up the experience for passengers, elevate the prestige of your properties and enjoy convenience at your fingertips with Dewhurst's premium multimedia display.

ATOM displays for all building types



Communicate or advertise to a captive audience

Leverage on undivided attention and monetise vacant wall space



Inform and entertain







Publish to one or grouped displays



Remote screen update with live view

Make your elevators and properties stand out





Stunning multimedia displays



Full HD screens

Best fit & flexible installation



7 screen sizes 10.4" to 21.5"



Vibrant 24-bit colour depth



Portrait or landscape mount



Up to 178° wide visibility



Dual-screen configuration



Speakers included



On board power supplies

Maximise uptime and enjoy peace of mind

Real time monitoring and reports

- Uptime and event log
- Proof of play analytics
- Status across building and sites

Alerts, remote diagnosis and troubleshooting

- Live display view
- Remote reboot
- Network connection check
- Remote firmware updates
- Email notifications

Technical Specification

SCREEN SIZE	10.4"	12.1"	15.0"	15.6"	18.5"	21.5"
				OF-156-914H	OF-185-914H	OF-215-914H
Model No.	ATOM01-104-	ATOM01-121-	ATOM01-150-	& ATOM01-	& ATOM01-	& ATOM01-
Model No.	7-40-940	7-40-940	7-40-940	000-0-40-	000-0-40-	000-0-40-
				900	900	900

DISPLAY

LCD display type			Thin	Film Transistor (TF	T)	
Colour depth	True Colour (24-bit colour)					
Resolution	1024 x 768	1024 x 768	1024 x 768	1920 x 1080	1920 x 1080	1920 x 1080
Aspect ratio	4:3	4:3	4:3	16:9	16:9	16:9
Viewing area (W x H) (mm)	211 x 158	246 x 185	304 x 228	344 x 194	409 x 230	477 x 268
Horizontal viewing angle (°)	+88/-88	+88/-88	+85/-85	+89/-89	+89/-89	+89/-89
Vertical viewing angle (°)	+88/-88	+88/-88	+85/-85	+89/-89	+89/-89	+89/-89
Luminance	400	500	270	400	350	300
Contrast ratio	700:1	1200:1	1500:1	800:1	1000:1	5000:1

ELECTRICAL & ENVIRONMENTAL

Operating voltage (VDC)				12~24V DC			
Typical current consumption (A) Main/Aux display	1.38/0.5	1.54/1	1.71/0.92	0.71/1.42	0.71/1.67	0.71/1.17	
Typical power consumption (W) Main/Aux display	16.5/6	18.5/12	20.5/11	8.5/17	8.5/20	8.5/14	
Operating temperature (°C)				0 < 50			
Humidity range (%RH)				10 < 90			
Backlight MTBF (Hrs)				50,000			

MECHANICAL

Mounting options				Flush Mount			
Overall dimensions	280 x 235 x 38	290 x 240 x 38	357 x 289 x 37.5	202 x 277.5 x 23			
	Main screen			Central Processing Unit (CPU)			
(W x H x D mm)	280 x 235 x 30	290 x 240 x 30	357 x 289 x 30	398 x 222 x 38	494 x 270 x 40	435 x 380 x 40	527 x 338 x 38
	Auxillary screen, if required			Auxillar	y screen		

COMMUNICATION & I/O INTERFACES

Signal interface	E-Motive 4-Wire, MKCAN
Network interface	Ethernet (RJ45)
I/O interface	DC-In, DC-Out, HDMI, USB, Audio-Out

Ordering information

MAIN MODULE

Part no.	Product description
ATOM01-104-7-40-940	ATOM Multimedia Display 10.4"
ATOM01-121-7-40-940	ATOM Multimedia Display 12.1"
ATOM01-150-7-40-940	ATOM Multimedia Display 15"
ATOM01-000-0-40-900	ATOM Multimedia CPU Module

Open frame

Part no.	Product description
OF-104-914H	Open Frame Display 10.4"
OF-121-914H	Open Frame Display 12.1"
OF-150-914H	Open Frame Display 15"
OF-156-914H	Open Frame Display 15.6"
OF-185-914H	Open Frame Display 18.5"
OF-215-914H	Open Frame Display 21.5"

Note 1: Each ATOM Multimedia product includes switching PSU and 16ohm speakers

Note 2: Each ATOM Open Frame product includes switching PSU and 5m HDMl cable

Note 3: Open Frame displays will also require ATOM Multimedia CPU Module (sold separately)

Note 4: Each ATOM Multimedia product and Open Frame come with Lens included

ACCESSORIES AVAILABLE

Part no.	Product description
133-C-0-0308	HDMI Cable, 5m
133-C-1-0229	USB Extension Cable, 5m
147-2-0-0041	Ethernet Router
147-2-0-0039	Ethernet Switch, 8-Port
147-2-1-0039	Ethernet Switch, 16-Port
SOFTWARE-CD	ATOM Software

Part no.	Product description
147-1-1-0042	Ethernet/VDSL Converter
147-1-0-0038	Ethernet/Fibre Optics Converter
VSERVER-MINI	Video Server Mini
VSERVER-MAX	Video Server Max
ML4031OO001	4-Input/1-Output 4-Wire Concentrator

DEWHURST FOR YOUR ELEVATOR DISPLAY NEEDS



Proven in thousands of worldwide installations



Industrial-grade performance & durability



Local sales & technical support



Global expertise in lift solutions

www.dewhurst.co.uk displays@dewhurst-global.com



We operate a policy of continuous product development and reserve the right to change or improve specification without prior notice. E & OE.

All information within this document is for guidance only and does not form the basis for contract. The product images and diagrams shown are for illustration purposes only and may not be an exact representation of the latest version of the product. ©2023 Dewhurst. All Rights Reserved.

Please consider the environment before you print this document.



Access the Dewhurst
ATOM webpage for
more information

